

# EM-201 Stereo Compact Amplifier 2x35W – Wireless

## HIGHLIGHTS

- ✓ Wireless
- ✓ Analogue Alim. and Ampli.
- ✓ Coaxial and optic inputs
- ✓ USB input (Type-A)
- ✓ Headphone output 6,35mm
- ✓ Subwoofer output

## LOGISTICAL DATA

**EAN Code**  
Black: 0634654606150

**DEEE**  
4.4 = 0,84 € H.T. = 1 € T.T.C.

**Dimensions (WxHxD) & Weight PRODUCT**  
280 x 80 x 200 mm / 4 Kg

**PACKAGING**  
340 x 150 x 320 mm / 4.5 Kg



This amplifier EM-201 was designed in an audiophile approach to ensure the high fidelity amater a faithful reproduction of his favourite music. It delivers 2x25W RMS into 8Ω and 2x35W into 4Ω.

It includes a Wireless interface, allowing you to play music from your Smartphones or tablets. The EM-201 comes with 4 unbalanced audio inputs including a USB that allows you to play your digital files stored on USB key in MP3 and WMA formats and including one digital input (coaxial and/or optical) allowing connection to latest generation TV sets.

The EM-201 offers a Subwoofer output to connect an active subwoofer. This output is coupled with a "Large / Small" selector allowing activate a high-pass filter to optimize your listening in 2.1.

### MAIN FEATURES

- High quality manufacturing
- Analogue power supply and amplification (from EX222)
- Large power output amplifier stage for both channels (150VA)

- WIRELESS connection with removable antenna
- Optical and Coaxial digital inputs
- USB input
- Jack 6.35 mm Headphone output

### Readable files via USB:

- MP3
- Format: MPEG-1 Audio Layer 3
- Sampling frequency: 44.1 ou 48 kHz
- Bit rate: 320 kb/s or less
- WMA
- Sampling frequency: 44.1 kHz
- Bit rate: 192 kb/s or less

### Included Accessories

- 1x Detachable IEC power cord
- 1x Wireless antenna
- 1x Manual

**Digital Inputs:** The OPTICAL connector will override the source connected to COAXIAL, unless the source connected to the optical connector is turned off. In this case, you can listen to the source connected in coaxial.

## SPECIFICATIONS

### Amplifier section

Power: 2x25W into 8Ω,  
2x35W into 4Ω (1kHz, 1%)  
Total harmonic distortion < 0,2%  
Bandwidth : 20Hz-20kHz  
Signal to noise ratio > 70dBA  
Speaker Impedance compatibility range: 4-8Ω

« Large/Small » selector to activate a high-pass filter at 100Hz.

### USB port :

Type-A  
Recognized format: FAT

### WIRELESS :

Range: about 10 m

### Connectors :

- 1x Headphone (Jack 6.35 mm)
- 1x USB input (Type-A)
- 2x RCA line inputs
- 1x Coaxial input
- 1x Optical input
- 1x Subwoofer output
- 1x Wireless antenna
- 1x Detachable IEC power cord
- 4x Screw terminals compatible with banana plugs