

EX-242 Stereo Integrated Amplifier 2x90W - Wireless

HIGHLIGHTS

- ✓ Wireless
- ✓ Coaxial and optical inputs
- ✓ MP3, USB, PHONO input
- ✓ Headphone and pre-out output
- ✓ Sub and filter

LOGISTICAL DATA

EAN Code
Black: 0634654606211

DEEE
4.4 = 0,84 € H.T. = 1 € T.T.C.

Dimensions (WxHxD) & Weight PRODUCT
430 x 111 x 461 mm / 11.8 Kg

PACKAGING
520 x 200 x 560 mm / 14.1 Kg



This amplifier EX-242 was designed in an audiophile approach to ensure the high fidelity amater a faithful reproduction of his favourite music. It delivers 2x90W RMS into 8Ω, thanks to its high-performance 2x140W into 4Ω.

It includes a WIRELESS interface, allowing you to play music from your Smartphones. The EX-242 comes with 4 unbalanced audio inputs including a 3,5 mini jack MP3 input, one PHONO, one USB and one digital input (coaxial and/or optical), allowing connection to latest generation TV sets.

Finally, it provides a « pre-out » to perform bi-amplification.

MAIN FEATURES

- High quality manufacturin
- Shielded preamplifier
- Large power supply (500VA)
- Stage power generously dimensioned consequences: ability to drive any kind of speakers (8, 4, 3 Ohms).

- WIRELESS with removable antenna
- Optical (2) and Coaxial (2) digital inputs
- MP3 input 3,5mm
- Headphone output 6.35mm

Included Accessories

- 1x Detachable IEC power cord
- 1x Wireless antenna
- 1x Remote control RC-EX4
- 1x Battery CR2025 for remote control
- 1x Manual

DAC: The S/PDIF input is interfaced to a Cirrus Logic CS8416 chip and analog digital conversion is supported by a PCM1973 circuit from the same manufacturer. Maximum sampling is 24 bits at 96 kHz on the coaxial and optical inputs.

Digital Inputs: The OPTICAL connector will override the source connected to COAXIAL, unless the source connected to the optical connector is turned off. In this case, you can listen to the source connected in coaxial.

SPECIFICATIONS

Amplifier section

Power: 2x90W RMS into 8 Ω
and 2x140W into 4 Ω
Total harmonic distortion < 0,01%
Signal to noise ratio > 100 dBA
Bandwidth: 20 Hz - 20 KHz
Speaker Impedance Compatibility
Range : 3-8 Ω

Wireless

Range: about 10 m

Connectors

2x RCA line inputs (LINE 1 et LINE 2)
1x Phono input (LINE 2)
2x Optical input
2X Coaxial input
1x Output line (LINE)
1x Output REC
1x MP3 input (Mini-jack 3. 5 mm)
1x Headphone Jack 6.35 mm in front
1x Wireless antenna
8x Screw terminals compatible with banana plugs