

EX-502 Power Amplifier 2x170W / 4Ω



HIGHLIGHTS

- ✓ 2x100w/170 (8/4Ω)
- ✓ 2x settings detachable volumes
- ✓ RCA and High-level inputs



The power amplifier EX502 has been designed to meet the needs of amateur music or cinema. It will complement all facilities enabling them to achieve significant levels of power while maintaining a high quality musicality.

As part of a bi-amplification, it will drive any kind of speakers, including the ones that's need a lot of power. Level variable gain allows it to adapt to all possible configurations. As part of an AV installation, he is very advantageously complement an AV amplifier supports the main speakers..

MAIN FEATURES

- High quality manufacturing
- 2 settings detachable volumes
- High-end components (Transistors Toshiba 2SC5200/2SA1943)
- 500VA massive toroidal transformer

- Auto Standby
- Controlled by trigger

SPECIFICATIONS

Continuous average output power into 8Ω
2x 100 W in stereo mode
1x 300 W in mono mode

into 4Ω
2x 170 W in stereo mode
1x 360 W in mono mode

Distorsion: 0,08% (20 Hz - 20 KHz)
Signal to noise ratio > 90 (1W)

Connectors

1x RCA stereo input or High-level input on speaker terminals.
Sensitivity: 1.2 V (2x80W/8Ω)
Impedance: 45Ω
Maximum input level: 5V
8x Speakers terminals
1x Trigger (auto/on)

Included Accessories

1x Detachable IEC power cord
1x Manual

LOGISTICAL DATA

EAN Code
Black: 0628586586529

DEEE
4.4 = 0,84 € H.T. = 1 € T.T.C.

Dimensions (WxHxD) & Weight
PRODUCT
430 x 70 x 360 mm / 9.5 Kg

PACKAGING
490 x 140 x 445 mm / 10.6 Kg